## CHEVROLET (USA / CAN) TRAVERSE GMT561 TRAVERSE 3.6 V6 AWD (2012-2012)



ENGINE LLT Capacity: 5,7 liter	
USE	CLIMATE
Flexible (max)	Arctic
PRODUCT RECOMMENDATION 1	
Presteza MSP 5W-30	
Change avery ZEOO miles/ 12 months	

Change every 7500 miles/ 12 months

DIFFERENTIAL REAR (4x4)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
	•

Check every 7500 miles

TRANSAXLE AUTOMATIC 6/1 Capacity: 5 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
Check every 7500 miles, change every 97	500 miles	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		

SP Matic 4036

Check every 7500 miles, change every 45000 miles

## CHEVROLET (USA / CAN) TRAVERSE GMT561 TRAVERSE 3.6 V6 AWD (2012-2012)



TRANSFERBOX (4X4) Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 7500 miles, change every 97	500 miles	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 7500 miles, change every 45	000 miles	

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 7500 miles, change every 45000 miles/ 36 months		

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	

Check every 7500 miles

COOLING SYSTEM Capacity: 10,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	
Check every 7500 miles, change every 150000 miles/ 60 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.