CHEVROLET (USA / CAN) UPLANDER UPLANDER 3.5 V6 (2006-2008)



ENGINE LX9 Capacity: 4,3 liter, Filter capacity: 0,5 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Presteza MSP 5W-30	Xedoz FE 5W-30	

Change every 12 months

TRANSAXLE AUTOMATIC 4/1 Capacity: 7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Check every 12 months, change every 10	000 miles
USE	CLIMATE

Severe Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

Check every 12 months, change every 50000 miles

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	

CHEVROLET (USA / CAN) UPLANDER UPLANDER 3.5 V6 (2006-2008)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 12 months		

COOLING SYSTEM Capacity: 10,7 liter (+ airconditioning), Capacity: 12,2 liter (+ rear airconditioning)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Coolant SP 15	Coolant SP 15+			
Check every 12 months, change every 150000 miles/ 60 months				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.