CHRYSLER (USA / CAN) 300 LX 300 3.6 V6 (2014 AND AFTER)



ENGINE Pentastar Capacity: 5,6 liter	
USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Duranza ECO 5W-20	
Change every 10000 miles/ 12 months	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Duranza ECO 5W-20	
Characta avera (1000 miles	

Change every 4000 miles

DIFFERENTIAL REAR Capacity: 0,7-1,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	
Check every 20000 miles/ 24 months	

USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	
Change every 50000 miles/ 60 months	

TRANSMISSION AUTOMATIC 845RE 8/ Capacity: 9,2 liter (Dry fill)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2034	

TRANSMISSION AUTOMATIC 8HP50 850RE 8/1		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2034		

CHRYSLER (USA / CAN) 300 LX 300 3.6 V6 (2014 AND AFTER)



HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

COOLING SYSTEM Capacity: 9,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		
01 150000 11 (100			

Change every 150000 miles/ 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.