

CHRYSLER (USA / CAN) 300 LX 300 6.4 HEMI V8 SRT8 (2011-2012)



ENGINE HEMI
Capacity: 6,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

Change every 6000 miles/ 6 months

DIFFERENTIAL REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear LS 1015

Check every 18000 miles/ 18 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Gear LS 1015

Change every 48000 miles/ 48 months

TRANSMISSION AUTOMATIC W5A580 5/1

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Change every 120000 miles/ 120 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Change every 60000 miles/ 60 months

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

CHRYSLER (USA / CAN) 300 LX 300 6.4 HEMI V8 SRT8 (2011-2012)



POWER STEERING

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

COOLING SYSTEM

Capacity: 14,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO*Change every 102000 miles/ 60 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.