

CHRYSLER (USA / CAN) 300(C) LX 300C 5.7 HEMI V8 AWD (USA) (2006-2008)

**ENGINE**

Capacity: 6,6 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Duranza ECO 5W-20***Change every 6000 miles/ 6 months***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Duranza ECO 5W-20***Change every 3000 miles/ 3 months***DIFFERENTIAL FRONT**

Capacity: 0,6 liter

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90****PRODUCT RECOMMENDATION 3****Syngear 75W-90***Change every 48000 miles***DIFFERENTIAL REAR****USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube Racing 75W-140****PRODUCT RECOMMENDATION 2****Gearlube HS GL-5 80W-140***Change every 48000 miles***TRANSFERBOX MS140**

Capacity: 0,6 liter

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 2032***Change every 48000 miles*

CHRYSLER (USA / CAN) 300(C) LX 300C 5.7 HEMI V8 AWD (USA) (2006-2008)



TRANSMISSION AUTOMATIC NAG1 (W5A580)
Capacity: 7,7 liter (Overhaul capacity), Capacity: 5 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 120000 miles/ 120 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 60000 miles

HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

COOLING SYSTEM
Capacity: 13,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Change every 102000 miles/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.