

PRODUCT RECOMMENDATION

CHRYSLER (USA / CAN) 300M LH 300M 3.5 (USA) (1998-2004)



ENGINE SOHC
Capacity: 4,7 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| | | |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 | | |
| Asyntho 5W-30 | | |

Change every 6000 miles/ 6 months

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

| | | |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 | | |
| Asyntho 5W-30 | | |

Change every 3000 miles

DIFFERENTIAL FROM AUTOMATIC
Capacity: 0,95 liter

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

| | | |
|--------------------------|---------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011 | Syngear TDL 75W-90 | Syngear 75W-90 |

Change every 48000 miles

TRANSMISSION AUTOMATIC 4/1
Capacity: 9,4 liter

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

| | | |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4026 | | |

Change every 60000 miles

HYDRAULIC BRAKE SYSTEM

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| | | |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid DOT 3 | | |

CHRYSLER (USA / CAN) 300M LH 300M 3.5 (USA) (1998-2004)



POWER STEERING

Capacity: 0,7 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4026 | | |

Change every 60000 miles

COOLING SYSTEM

Capacity: 7,8-8,9 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 12 EVO | | |

Change every 102000 miles/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.