## CHRYSLER (EU) DELTA DELTA 1.6 16V MJET (88 KW) (2011-2014)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Avanza MSP+ 5W-30	Avanza RPC 5W-30

Change every 24 months

TRANSAXLE MANUAL C530.6 6/ Capacity: 2,55 liter (Dry fill), Capaci		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	
Check every 35000 km	,	,

TRANSAXLE SEMI-AUTOMATIC C5 Capacity: 2,55 liter (Dry fill), Capacity:		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
Check every 35000 km	1	1

TRANSAXLE SEMI-AUTOMATIC Capacity: 1,9 liter	C635 DDCT 6/1		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1081	SP Gear 5015		
Check every 35000 km			

HYDRAULIC BRAKE SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change every 35000 km/ 24 months		·	

## CHRYSLER (EU) DELTA DELTA 1.6 16V MJET (88 KW) (2011-2014)



COOLING SYSTEM Capacity: 5,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 35000 km	'	,

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.