

# CHRYSLER (USA / CAN) SEBRING JR

## SEBRING 2.4 16V (USA) (2003-2006)

**ENGINE**

Capacity: 4,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Presteza MSP 5W-30</b>	<b>Xedoz FE 5W-30</b>

*Change every 6000 miles/ 6 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Presteza MSP 5W-30</b>	<b>Xedoz FE 5W-30</b>

*Change every 3000 miles/ 3 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 3,8 liter (Service fill)

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	
<b>SP Matic 4026</b>	

*Change every 60000 miles***TRANSAXLE MANUAL NV T350 5/1**

Capacity: 2,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>SP Matic 4026</b>	

**HYDRAULIC BRAKE SYSTEM ABS**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>Drauliquid DOT 3</b>	

# CHRYSLER (USA / CAN) SEBRING JR

## SEBRING 2.4 16V (USA) (2003-2006)



### POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 4026</b>		

### COOLING SYSTEM

Capacity: 7,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 12 EVO</b>		

*Change every 102000 miles/ 60 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*