

CITROËN BX BX 18 TURBO DIESEL (1989-1993)



ENGINE

Capacity: 5,5 liter, Filter capacity: 0,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Bi-Turbo 15W-40*Check every 3000 km, change every 10000 km/ 12 months*

USE

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

Emperol 10W-40*Check every 3000 km, change every 10000 km/ 12 months*

TRANSAXLE AUTOMATIC

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 10000 km, change every 40000 km*

TRANSAXLE MANUAL 5/1

Capacity: 2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80*Check every 10000 km*

HYDRAULIC SYSTEM POWER STEERING/BRAKE BOOSTER/LEVELLING

Capacity: 4,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

LHM +*Change every 60000 km*

CITROËN BX BX 18 TURBO DIESEL (1989-1993)

**COOLING SYSTEM**

Capacity: 6,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF*Change every 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.