CITROËN C2 C2 1.6 16V (80 KW) (2009-2010)



ENGINE TU5JP4 Capacity: 3,25 liter, Filter capacity:	0,25 liter	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30
Check every 2000 km, change ever	ry 30000 km/ 24 months	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30
Change every 20000 km/ 12 month	S	,

TRANSAXLE AUTOMATED MA5	P 5/1	
USE		CLIMATE
Filled for life		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	
Check every 60000 km		

HYDRAULIC BRAKE SYSTEM ABS			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Check every 30000 km, change every	24 months		

COOLING SYSTEM Capacity: 7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	
Check every 24 months/ 30000 km	

AIRCONDITIONING COMPRESSOR Capacity: 135 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

CITROËN C2 C2 1.6 16V (80 KW) (2009-2010)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.