

**CITROËN C4 C4 1.4 16V (2009-2010)**

**ENGINE ET3J4**  
Capacity: 3 liter

| USE                      |                           | CLIMATE                  |
|--------------------------|---------------------------|--------------------------|
| Normal                   |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>Avanza MSP 0W-30</b>  | <b>Presteza MSP 5W-30</b> | <b>Avanza MSP+ 5W-30</b> |

*Change every 30000 km/ 24 months*

| USE                      |                           | CLIMATE                  |
|--------------------------|---------------------------|--------------------------|
| Severe                   |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>Avanza MSP 0W-30</b>  | <b>Presteza MSP 5W-30</b> | <b>Avanza MSP+ 5W-30</b> |

*Change every 20000 km*

**TRANSAXLE MANUAL MA5 5/1**  
Capacity: 2,1 liter (Dry fill), Capacity: 2 liter (Service fill)

| USE                      |                            | CLIMATE  |
|--------------------------|----------------------------|----------|
| Normal                   |                            | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2   |          |
| <b>SP Gear 5015</b>      | <b>Gearlube RPC 75W-80</b> |          |

*Check every 24 months/ 30000 km*

**HYDRAULIC BRAKE SYSTEM ABS**

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

*Change every 24 months*

**POWER STEERING**

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Fluid 3013</b>     |  |          |

*Check every 24 months/ 30000 km*

**CITROËN C4 C4 1.4 16V (2009-2010)****COOLING SYSTEM**

Capacity: 5,8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

**PRODUCT RECOMMENDATION 1****Coolant SP 14+***Check every 24 months/ 30000 km***AIRCONDITIONING COMPRESSOR**

Capacity: 135 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*