CITROËN C5 X7 C5 1.6 HDI DPF 9HL (2010-2011)



ENGINE DV6C Capacity: 3,75 liter (Service fill), Filter capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30

Change every 20000 km/24 months

Capacity: 5,85 liter (Dry fill), Capacity: 3 liter (Service fill)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	

TRANSAXLE AUTOMATIC AM6 6/1 Capacity: 7 liter (Dry fill), Capacity: 3 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
0		

Check every 60000 km/ 24 months

TRANSAXLE AUTOMATIC AT6 6/1 Capacity: 7 liter (Dry fill), Capacity: 3 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
Chack ayon, 60000 km/24 months		

Check every 60000 km/24 months

TRANSAXLE MANUAL MCM 6/1 Capacity: 2,2 liter (Dry fill), Capacity: 2,1 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	
Check every 60000 km/24 months	·	·

PRODUCT RECOMMENDATION

CITROËN C5 X7 C5 1.6 HDI DPF 9HL (2010-2011)



HYDRAULIC SYSTEM POWER STEERING/LEVELLING Capacity: 4,3 liter		
use Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 SP Fluid 3013		

Check every 20000 km/24 months, change every 200000 km/60 months

CLIMATE
Moderate
2

Check every 20000 km/24 months, change every 60000 km/24 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 20000 km/ 24 months		

COOLING SYSTEM Capacity: 0-0 liter (Between min and max.	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	

PARTICLE FILTER ADDITIVE SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.