

CITROËN C5 X7 C5 1.6 THP 155 (115 KW)

(2009-2011)

**ENGINE EP6DT**

Capacity: 4,25 liter, Filter capacity: 0,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Avanza MSP 0W-30*Change every 30000 km/ 24 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Avanza MSP 0W-30*Change every 20000 km/ 12 months***TRANSAXLE AUTOMATED MCP 6/1**

Capacity: 2,2 liter (Dry fill), Capacity: 2,1 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80*Check every 60000 km/ 24 months***TRANSAXLE AUTOMATIC AL4 4/1**

Capacity: 5,85 liter (Dry fill), Capacity: 3 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032**TRANSAXLE AUTOMATIC AM6 6/1**

Capacity: 7 liter (Dry fill), Capacity: 3 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 60000 km/ 24 months*

CITROËN C5 X7 C5 1.6 THP 155 (115 KW) (2009-2011)

**TRANSAXLE AUTOMATIC AT6 6/1**

Capacity: 7 liter (Dry fill), Capacity: 3 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 60000 km/ 24 months***TRANSAXLE MANUAL MCM 6/1**

Capacity: 2,2 liter (Dry fill), Capacity: 2,1 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80*Check every 60000 km/ 24 months***HYDRAULIC ACTUATION MCP GEARBOX**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3023**HYDRAULIC SYSTEM POWER STEERING/LEVELLING**

Capacity: 4,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013*Check every 24 months/ 30000 km***HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Check every 30000 km, change every 24 months*

CITROËN C5 X7 C5 1.6 THP 155 (115 KW) (2009-2011)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 24 months/ 30000 km

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 24 months/ 30000 km

AIRCONDITIONING COMPRESSOR

Capacity: 135 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 625 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.