

**CITROËN C5 C5 1.8i 16V (2005-2009)****ENGINE EW7A (6FY)**

Capacity: 5 liter

| USE                           |                          | CLIMATE                  |
|-------------------------------|--------------------------|--------------------------|
| Normal                        |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Specialsynth MSP 5W-40</b> | <b>Emperol 5W-40</b>     | <b>Asyntho 5W-30</b>     |

*Change every 30000 km/ 24 months*

| USE                           |                          | CLIMATE                  |
|-------------------------------|--------------------------|--------------------------|
| Severe                        |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Specialsynth MSP 5W-40</b> | <b>Emperol 5W-40</b>     | <b>Asyntho 5W-30</b>     |

*Change every 20000 km/ 12 months***TRANSAXLE MANUAL BE4/5 5/1**

Capacity: 1,9 liter (Dry fill), Capacity: 1,8 liter (Service fill)

| USE                      |                            | CLIMATE  |
|--------------------------|----------------------------|----------|
| Normal                   |                            | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2   |          |
| <b>SP Gear 5015</b>      | <b>Gearlube RPC 75W-80</b> |          |

*Check every 60000 km/ 24 months***HYDRAULIC SYSTEM POWER STEERING/LEVELLING**

Capacity: 4,3 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Fluid 3013</b>     |  |          |

*Check every 30000 km, change every 24 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

*Check every 30000 km, change every 24 months*

**CITROËN C5 C5 1.8I 16V (2005-2009)****GREASE POINTS/NIPPLES**

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Check every 24 months/ 30000 km

**COOLING SYSTEM**

Capacity: 8 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 14+</b>    |  |          |

Check every 24 months/ 30000 km

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*