CITROËN C5 C5 2.2 HDI 16V (2000-2005)



ENGINE DW12TED4/4HX Capacity: 4,75 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30

Change every 20000 km/24 months

TRANSAXLE AUTOMATIC 4HP20 4/1 Capacity: 8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
Check every 20000 km/ 24 months		

TRANSAXLE MANUAL ML5T 5/1 Capacity: 1,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	
Check every 60000 km/24 months	'	

HYDRAULIC SYSTEM POWER STEERING/LEVELLING Capacity: 4,3 liter		
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 SP Fluid 3013		

Check every 20000 km/24 months, change every 200000 km/60 months

YDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 20000 km/24 months, change every 60000 km/24 months		

CITROËN C5 C5 2.2 HDI 16V (2000-2005)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 20000 km/ 24 months		

COOLING SYSTEM		

Coolant SP 14+	
PRODUCT RECOMMENDATION 1	
Normal	Moderate
USE	CLIMATE
Capacity: 11 liter	

Check every 20000 km/24 months, change every 120000 km/60 months

PARTICLE FILTER ADDITIVE SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.