CITROËN XANTIA XANTIA 2.0I 16V (1993-1994)



ENGINE XU10J4D/Z Capacity: 4,25 liter, Filter capacity: 0,5 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30		

Check every 3000 km, change every 10000 km/12 months

TRANSAXLE MANUAL 5/1 Capacity: 1,9 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	Gearlube RPC 75W-80		
Check every 10000 km/ 12 months		,	

HYDRAULIC SYSTEM Capacity: 5,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
LHM +	
Check every 10000 km, change every 60	m

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
Check every 10000 km			

COOLING SYSTEM Capacity: 7,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Chack avany 10000 km/12 months, change avany 24 mon	

Check every 10000 km/12 months, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

CITROËN XANTIA XANTIA 2.0I 16V (1993-1994)



information contained herein is subject to changes without notification.