

CITROËN XSARA XSARA 2.0i 16V VTS (1999-2005)



ENGINE XU10J4RS
Capacity: 4,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30

Change every 20000 km/ 12 months

TRANSAXLE MANUAL 5/1
Capacity: 1,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	

Check every 20000 km/ 12 months

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 20000 km/ 12 months, change every 60000 km/ 24 months

HYDRAULIC BRAKE SYSTEM ABS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 20000 km/ 12 months, change every 60000 km/ 24 months

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 20000 km/ 12 months

CITROËN XSARA XSARA 2.0i 16V VTS (1999-2005)



COOLING SYSTEM

Capacity: 7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

Check every 20000 km/ 12 months, change every 120000 km/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.