## **DAIHATSU CHARADE CHARADE 1.3** (1988-1993)



| <b>ENGINE</b> HC-C Capacity: 3,5 liter, Filter capacity: 0,2 liter |                           |               |
|--|---------------------------|---------------|
| USE  |                           | CLIMATE       |
| Normal   |                           | Mediterranean |
| PRODUCT RECOMMENDATION 1   |                           |               |
| HDX 20W-50   |                           |               |
| Change every 10000 km/ 6 months                                    |                           |               |
| USE  |                           | CLIMATE       |
| Normal   |                           | Moderate      |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2  |               |
| Emperol 10W-40   | Classic Racing Oil 15W-50 |               |
| Change every 10000 km/ 6 months                                    |                           |               |
| USE  |                           | CLIMATE       |
| Normal   |                           | Cold          |
| PRODUCT RECOMMENDATION 1   |                           |               |
| Asyntho 5W-30  |                           |               |
| Change every 10000 km/ 6 months                                    |                           |               |

| TRANSAXLE AUTOMATIC 3/1<br>Capacity: 2 liter |                          |  |
|--|--------------------------|--|
| USE  | CLIMATE                  |  |
| Normal                                       | Moderate                 |  |
| PRODUCT RECOMMENDATION 1                     |                          |  |
| ATF Dexron II-D                              |                          |  |
| Check every 10000 km/ 6 months, ca           | verv 80000 km/ 48 months |  |

| I IMATE                  |
|--------------------------|
| LIMATE                   |
| Moderate                 |
| PRODUCT RECOMMENDATION 3 |
| Syngear TDL 75W-90       |
|                          |

## **DAIHATSU CHARADE CHARADE 1.3** (1988-1993)



| HYDRAULIC BRAKE SYSTEM    |                          |                          |
|---------------------------|--------------------------|--------------------------|
| USE                       |                          | CLIMATE                  |
| Normal                    |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4       | Drauliquid DOT 3         |
|                           |                          |                          |

Change every 80000 km/ 48 months

| COOLING SYSTEM Capacity: 5,2 liter |          |
|------------------------------------|----------|
| USE                                | CLIMATE  |
| Normal                             | Moderate |
| PRODUCT RECOMMENDATION 1           |          |
| Coolant -38 Organic NF             |          |
| Change every 40000 km/ 48 months   |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.