

DAIHATSU ROCKY / FOURTRACK ROCKY / FOURTRACK 2.2 (1994-2003)

**ENGINE 3Y**

Capacity: 4 liter, Capacity: 4,6 liter (Dry fill), Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

HDX 20W-50*Change every 10000 km/ 6 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Emperol 10W-40

PRODUCT RECOMMENDATION 2

Classic Racing Oil 15W-50*Change every 10000 km/ 6 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 10000 km/ 6 months*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

HDX 20W-50*Change every 5000 km/ 6 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Emperol 10W-40

PRODUCT RECOMMENDATION 2

Classic Racing Oil 15W-50*Change every 5000 km/ 6 months*

USE	CLIMATE
Severe	Cold

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 5000 km/ 6 months*

DAIHATSU ROCKY / FOURTRACK ROCKY / FOURTRACK 2.2 (1994-2003)



DIFFERENTIAL FRONT

Capacity: 1,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

DIFFERENTIAL REAR

Capacity: 1,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

TRANSFERBOX

Capacity: 1,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

TRANSMISSION MANUAL 5/1

Capacity: 2,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90

Check every 10000 km/ 6 months, change every 30000 km/ 18 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Change every 12 months

DAIHATSU ROCKY / FOURTRACK ROCKY / FOURTRACK 2.2 (1994-2003)



POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 10000 km/ 6 months

GREASE POINTS/NIPPLES WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 40000 km/ 48 months

COOLING SYSTEM

Capacity: 7,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 40000 km/ 48 months

STEERING BOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-4 80W-90		

Check every 20000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.