FIAT (EU) 500 312 500 1.3 MULTIJET (55 KW) (2007-2016)



ENGINE 169A1000 Capacity: 3 liter (Service fill), Filter capacity: 0,2 liter				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30		
Check every 3000 km, change every 12 months				
USE		CLIMATE		
Flexible (max)		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30		

Check every 3000 km, change every 24 months

TRANSAXLE MANUAL 5/1 Capacity: 1,65 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 24 months

COOLING SYSTEM Capacity: 6,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	
Check every 20000 km/ 12 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.