

# FIAT (EU) BRAVO 198 BRAVO 1.6 MULTIJET (66 KW) (2013-2015)

**ENGINE 198A6000**

Capacity: 4,6 liter, Filter capacity: 0,3 liter

USE	CLIMATE
Flexible (max)	Moderate

## PRODUCT RECOMMENDATION 1

**Avanza MSP 0W-30***Change every 24 months***TRANSAXLE MANUAL C635 6/1**

Capacity: 1,87 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 1081**

## PRODUCT RECOMMENDATION 2

**SP Gear 5015****HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 525 grams (Dry fill)

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Check every 30000 km, change every 60000 km/ 24 months***GREASE POINTS/NIPPLES HOMOKINETIC JOINTS DIFFERENTIAL SIDE**

Capacity: 150 grams (Dry fill)

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gear Grease EP 0****GREASE POINTS/NIPPLES HOMOKINETIC JOINTS WHEEL SIDE**

Capacity: 120 grams (Dry fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

# FIAT (EU) BRAVO 198 BRAVO 1.6 MULTIJET (66 KW) (2013-2015)



## COOLING SYSTEM

Capacity: 7,1 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 14+**

Check every 30000 km

## AIRCONDITIONING

Capacity: 500 grams (Dry fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING COMPRESSOR Denso SCS 06

Capacity: 130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*