FIAT (EU) BRAVO 198 BRAVO 1.6 MULTIJET (77 KW) (2007-2010)



ENGINE 198A3000 Capacity: 4,6 liter, Filter capacity: 0,3 liter					
USE		CLIMATE			
Flexible (max)		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30			

Change every 24 months

TRANSAXLE MANUAL C635 6/1 Capacity: 1,87 liter (Dry fill)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 525 grams (Dry fill)				
	CLIMATE			
Normal				
PRODUCT RECOMMENDATION 2				
Drauliquid-S DOT 4				
	PRODUCT RECOMMENDATION 2	CLIMATE Moderate PRODUCT RECOMMENDATION 2		

Check every 30000 km, change every 60000 km/24 months

GREASE POINTS/NIPPLES HOMOKINETIC JOINTS DIFFERENTIAL SIDE Capacity: 150 grams (Dry fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Gear Grease EP 0				

GREASE POINTS/NIPPLES HOMOKINETIC JOINTS WHEEL SIDE

Capacity: 120 grams (Dry fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

FIAT (EU) BRAVO 198 BRAVO 1.6 MULTIJET (77 KW) (2007-2010)



COOLING SYSTEM Capacity: 7,1 liter (Dry fill)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Check every 30000 km		

AIRCONDITIONING

Capacity: 500 grams (Dry fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR Denso SCS 06 Capacity: 130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.