## FIAT (EU) CROMA 194 CROMA 1.9 MULTIJET (88 KW) DPF (2005-2010)



	CLIMATE
Flexible (max)	
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Avanza MSP+ 5W-30	Avanza RPC 5W-30

Change every 30000 km/ 12 months

TRANSAXLE MANUAL 6/1 Capacity: 1,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	
Check every 12 months/ 30000 km	<u> </u>

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS Capacity: 0,75 kg		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 30000 km, change every 60000 km/24 months

POWER STEERING Capacity: 0,63-0,72 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		
Check every 30000 km	'	

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Labora Grease	

## FIAT (EU) CROMA 194 CROMA 1.9 MULTIJET (88 KW) DPF (2005-2010)



## GREASE POINTS/NIPPLES HOMOKINETIC JOINTS DIFFERENTIAL SIDE

Capacity: 140 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The are arrable to give a startagra recommendation for this compensation related contact our convice apparation.			
GREASE POINTS/NIPPLES HOMOKINETIC JOINTS WHEEL	SIDE		
Capacity: 120 grams			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
MoS2 Grease EP 2			
GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Labora Grease			
GREASE POINTS/NIPPLES WHEEL BEARINGS REAR			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Labora Grease			
COOLING SYSTEM			
Capacity: 7,7 liter			
USE	CLIMATE		
Normal	Moderate		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 30000 km