

FIAT (EU) CROMA 194 CROMA 2.4 MULTIJET 20V (2005-2010)



ENGINE 939A3000
Capacity: 5,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Emperol 5W-40

Change every 30000 km/ 12 months

TRANSAXLE AUTOMATIC 6/1

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Check every 12 months/ 30000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS

Capacity: 0,75 kg

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Change every 60000 km/ 24 months

POWER STEERING

Capacity: 0,63-0,72 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013

Check every 12 months/ 30000 km

GREASE POINTS/NIPPLES FRONT SUSPENSION

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

FIAT (EU) CROMA 194 CROMA 2.4 MULTIJET 20V (2005-2010)



GREASE POINTS/NIPPLES HOMOKINETIC JOINTS DIFFERENTIAL SIDE

Capacity: 140 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES HOMOKINETIC JOINTS WHEEL SIDE

Capacity: 120 grams

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Labora Grease		

GREASE POINTS/NIPPLES WHEEL BEARINGS REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Labora Grease		

COOLING SYSTEM

Capacity: 8,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 12 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.