

FIAT (EU) DOBLÒ 223 DOBLÒ 1.9 MULTIJET (88 KW) DPF (2005-2009)

**ENGINE 186A9000**

Capacity: 4,3 liter, Filter capacity: 0,3 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30

Check every 1000 km, change every 30000 km/ 24 months

TRANSAXLE MANUAL 5/1

Capacity: 1,98 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	

Check every 80000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS

Capacity: 0,45 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 20000 km, change every 60000 km/ 24 months

POWER STEERING

Capacity: 1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 20000 km/ 12 months

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 20000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

FIAT (EU) DOBLÒ 223 DOBLÒ 1.9 MULTIJET (88 KW) DPF (2005-2009)



information contained herein is subject to changes without notification.