

FIAT (EU) PANDA 141 PANDA 750 (1986-1996)

**ENGINE 156A4.000**

Capacity: 3,75 liter, Filter capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Bi-Turbo 15W-40*Check every 500 km, change every 15000 km/ 6 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Check every 500 km, change every 15000 km/ 6 months***TRANSAXLE MANUAL**

Capacity: 2,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90*Check every 20000 km, change every 40000 km/ 24 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 500 km, change every 24 months***COOLING SYSTEM**

Capacity: 5,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF*Check every 500 km, change every 60000 km/ 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.