FIAT (EU) UNO 146 UNO 45 1.0 (1990-1993)



ENGINE 156A2.000 Capacity: 3,75 liter, Filter capacity: 0,4 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Bi-Turbo 15W-40			
Check every 500 km, change every 20000 km/ 12 months			
USE		CLIMATE	
Normal		Arctic	
PRODUCT RECOMMENDATION 1			
Asyntho 5W-30			
Check every 500 km, change every 20000 km/ 12 months			

TRANSAXLE MANUAL 4/1 Capacity: 2,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-4 80W-90	
Check every 20000 km, change every 120000 km	'

HYDRAULIC BRAKE SYSTEM Capacity: 0,37 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

COOLING SYSTEM Capacity: 4,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Check every 500 km, change every 24 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Check every 500 km, change every 12 months