FORD (EU) C-MAX MK I C-MAX 2.0 TDCI (2007-2010)



ENGINE G6DA (DW10) Capacity: 5,5 liter, Filter capacity: 0,5 liter		
use Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Duranza LSP 5W-30		

Change every 20000 km/ 12 months

TRANSAXLE MANUAL MMT6 6/1 Capacity: 1,75 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		
Check every 20000 km/ 12 months			

TRANSAXLE SEMI-AUTOMATIC MPS6/6DCT450 (PowerShift) 6/1		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 2072		

Check every 20000 km/ 12 months

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Observation 20000 line about the Control of the Con		

Check every 20000 km, change every 24 months

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
Check every 20000 km/ 12 months	

FORD (EU) C-MAX MK I C-MAX 2.0 TDCI (2007-2010)



COOLING SYSTEM Capacity: 6,5-7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 20000 km/ 12 months	c, change every 120 months	'

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.