

# FORD (EU) ESCORT ESCORT 1.8 DIESEL

## (1988-1998)

**ENGINE RT (OHC)**

Capacity: 5 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Emperol 10W-40***Check every 3000 km, change every 10000 km/ 12 months***TRANSAXLE MANUAL 5/1**

Capacity: 3,1 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 5015**

## PRODUCT RECOMMENDATION 2

**Gearlube GL-4 80W***Check every 20000 km/ 24 months***TRANSAXLE MANUAL MTX75 5/1**

Capacity: 2,6 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 5015***Check every 20000 km/ 24 months***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Change every 60000 km/ 36 months***POWER STEERING**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**SP Matic 4016**

## PRODUCT RECOMMENDATION 2

**ATF Dexron II-D***Check every 10000 km/ 12 months*

# FORD (EU) ESCORT ESCORT 1.8 DIESEL (1988-1998)

**COOLING SYSTEM**

Capacity: 9,3 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Coolant SP 11****PRODUCT RECOMMENDATION 2****Coolant -38 Organic NF***Change every 60000 km/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*