

FORD (EU) FIESTA MK VI FIESTA 1.25 16V (60 KW) (2012-2017)

**ENGINE** SNJB / SNJC / SNJD

Capacity: 4,1-4,4 liter (Dry fill), Capacity: 3,8-4 liter (Service fill), Filter capacity: 0,3 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| Duranza ECO 5W-20 | Duranza LSP 5W-30 | |

*Change every 20000 km/ 12 months***TRANSAXLE MANUAL** iB5 5/1

Capacity: 2,3 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Gear 1081 | | |

*Check every 20000 km/ 12 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|----------------------------------|--|--|
| Drauliquid-LV Super DOT 4 | | |

*Change every 24 months***COOLING SYSTEM**

Capacity: 5,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|-------------------------------|
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

*Check every 40000 km/ 12 months, change every 120 months***AIRCONDITIONING COMPRESSOR**

Capacity: 170 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR FROM 11.07.2016

Capacity: 170 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

FORD (EU) FIESTA MK VI FIESTA 1.25 16V (60 KW) (2012-2017)



AIRCONDITIONING SYSTEM

Capacity: 380-400 grams (with 12 mm condenser), Capacity: 510-530 grams (with 16 mm condenser)

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM FROM 11.07.2016

Capacity: 380-400 grams (with 12 mm condenser), Capacity: 510-530 grams (with 16 mm condenser)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.