## FORD (EU) FIESTA MK VI FIESTA 1.6 16V TI-VCT (88 KW) (2011-2012)



<b>ENGINE</b> HXJA Duratec Ti-VCT Capacity: 4,6 liter (Dry fill), Capacity: 4,05 liter (Service fill), Filter capacity: 0,3 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Duranza ECO 5W-20	Duranza LSP 5W-30			

Change every 20000 km/ 12 months

TRANSAXLE MANUAL iB5 5/1 Capacity: 2,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1081		
Check every 20000 km/ 12 months	·	

TRANSAXLE SEMI-AUTOMATIC DPS6/6DCT250 (PowerShift) 6/1 Capacity: 1,8 liter (Initial fill), Capacity: 1,5 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Gear 1081				
Check every 20000 km/ 12 months				

HYDRAULIC BRAKE SYSTEM FROM 02/2012 ONWARDS			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Drauliquid-LV Super DOT 4			
Check every 20000 km/ 12 months	'		

CLIMATE
Moderate

## FORD (EU) FIESTA MK VI FIESTA 1.6 16V TI-VCT (88 KW) (2011-2012)



COOLING SYSTEM Capacity: 5,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 20000 km/ 12 months, change every 120 months		

Check every 20000 km/12 months, change every 120 months

## AIRCONDITIONING COMPRESSOR Capacity: 170 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING SYSTEM

Capacity: 380-400 grams (with 12 mm condenser), Capacity: 510-530 grams (with 16 mm condenser)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.