PRODUCT RECOMMENDATION

FORD (EU) FOCUS C-MAX MK I FOCUS C-MAX 1.8 16V (2003-2007)

ENGINE CSDA/CSDB
Capacity: 4,6 liter (Initial fill), Capacity: 4,3 liter (Service fill), Filter capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Duranza ECO 5W-20	**Duranza LSP 5W-30**	

Change every 20000 km/ 12 months

TRANSAXLE AUTOMATIC CVT CFT23
Capacity: 8,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4016		

Check every 20000 km/ 12 months, change every 120000 km/ 72 months

TRANSAXLE MANUAL MTX75 5/1
Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	**Syngear TDL 75W-90**	

Check every 20000 km/ 12 months

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Check every 20000 km, change every 24 months

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Check every 20000 km/ 12 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

FORD (EU) FOCUS C-MAX MK I FOCUS C-MAX 1.8 16V (2003-2007)

COOLING SYSTEM Capacity: 6,5 liter		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Coolant SP 15+**	PRODUCT RECOMMENDATION 2 **Coolant SP 12**	PRODUCT RECOMMENDATION 3 **Coolant -38 Organic NF**
Check every 20000 km/ 12 months, change every 120 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367