

FORD (EU) FUSION FUSION 1.6 16V (2002-2005)

**ENGINE FYJA/FYJB**

Capacity: 4,3-4,5 liter (Initial fill), Capacity: 4,1-4,25 liter (Service fill), Filter capacity: 0,35-0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Duranza ECO 5W-20	Duranza LSP 5W-30	

Check every 1000 km, change every 20000 km/ 12 months

TRANSAXLE AUTOMATIC AW81-40 4/1

Capacity: 5,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Check every 20000 km/ 12 months

TRANSAXLE MANUAL iB5 5/1

Capacity: 2,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Check every 20000 km/ 12 months

HYDRAULIC BRAKE/CLUTCH SYSTEM MK60 ABS SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 20000 km, change every 24 months

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	

Check every 20000 km/ 12 months

FORD (EU) FUSION FUSION 1.6 16V (2002-2005)

**COOLING SYSTEM**

Capacity: 5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 20000 km/ 12 months, change every 120 months

AIRCONDITIONING COMPRESSOR

Capacity: 207 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 467-663 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.