## FORD (EU) GALAXY MK III (WA6) GALAXY 2.3 16V (2007-2010)



| <b>ENGINE</b> SEBA (Duratec HE) Capacity: 4,6 liter (Dry fill), Capacity: 4,3 liter (Service fill), Filter capacity: 0,4 liter |                          |          |  |  |
|--|--------------------------|----------|--|--|
| USE  |                          | CLIMATE  |  |  |
| Normal   |                          | Moderate |  |  |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2 |          |  |  |
| Duranza ECO 5W-20  | Duranza LSP 5W-30        |          |  |  |

Change every 20000 km/ 12 months

| TRANSAXLE AUTOMATIC AWF21 6/1 Capacity: 7 liter |    |          |
|---|----|----------|
| USE   | CI | LIMATE   |
| Normal  | M  | 1oderate |
| PRODUCT RECOMMENDATION 1                        |    |          |
| SP Matic 4026                                   |    |          |

| HYDRAULIC BRAKE SYSTEM    |          |
|---------------------------|----------|
| USE                       | CLIMATE  |
| Normal                    | Moderate |
| PRODUCT RECOMMENDATION 1  |          |
| Drauliquid-LV Super DOT 4 |          |
| Change every 24 months    | ·        |

| POWER STEERING           |  |          |
|--------------------------|--|----------|
| USE                      |  | CLIMATE  |
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| SP Fluid 3013            |  |          |

| COOLING SYSTEM Capacity: 6,2 liter |                          |                          |
|------------------------------------|--------------------------|--------------------------|
| USE                                |                          | CLIMATE                  |
| Normal                             |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1           | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+                     | Coolant SP 12            | Coolant -38 Organic NF   |
| Change every 120 months            | -                        | '                        |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.