

FORD (EU) GRAND C-MAX GRAND C-MAX

2.0 TDCI (120 KW) (2010-2014)

**ENGINE** TXDA Duratorq

Capacity: 6,45 liter (Dry fill), Capacity: 5,65 liter (Service fill), Filter capacity: 0,27 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Duranza LSP 5W-30*Change every 20000 km/ 12 months***TRANSAXLE MANUAL** MMT6 6/1

Capacity: 1,75 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081**TRANSAXLE SEMI-AUTOMATIC** MPS6/6DCT450 (PowerShift) 6/1

Capacity: 6-7,25 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2072*Change every 60000 km/ 36 months***HYDRAULIC BRAKE SYSTEM FROM 09/2011 ONWARDS**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Change every 24 months***HYDRAULIC CLUTCH SYSTEM**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Change every 24 months*

FORD (EU) GRAND C-MAX GRAND C-MAX 2.0 TDCI (120 KW) (2010-2014)


COOLING SYSTEM

Capacity: 8,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1
Coolant SP 15+
PRODUCT RECOMMENDATION 2
Coolant SP 12
PRODUCT RECOMMENDATION 3
Coolant -38 Organic NF*Change every 120 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.