

FORD (EU) KUGA I KUGA 2.0 TDCI (140) AWD EURO 5 (2011-2013)

**ENGINE UFMA**

Capacity: 5,6 liter (Dry fill), Capacity: 5,5 liter (Service fill), Filter capacity: 0,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Duranza LSP 5W-30***Change every 20000 km/ 12 months***DIFFERENTIAL REAR****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90***Check every 60000 km/ 36 months***TRANSAXLE AUTOMATIC AW55 AWD 5/1**

Capacity: 7,5-7,9 liter (+ cooler)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 4026***Change every 60000 km/ 36 months***TRANSAXLE MANUAL M66 6/1**

Capacity: 2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1081***Check every 20000 km/ 12 months***TRANSAXLE MANUAL MMT6 6/1**

Capacity: 1,75 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1081***Check every 20000 km/ 12 months*

FORD (EU) KUGA I KUGA 2.0 TDCI (140) AWD EURO 5 (2011-2013)


TRANSAXLE SEMI-AUTOMATIC MPS6/6DCT450 (PowerShift) 6/1

Capacity: 6-7,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2072*Change every 60000 km/ 36 months*
TRANSFERBOX (4x4)

Capacity: 0,45 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90
HYDRAULIC BRAKE SYSTEM FROM 09/2011 ONWARDS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Change every 24 months*
HYDRAULIC CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4
POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013

FORD (EU) KUGA I KUGA 2.0 TDCI (140) AWD EURO 5 (2011-2013)

**COOLING SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 20000 km/ 12 months, change every 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.