## FORD (EU) MONDEO MK I+II MONDEO 1.8I 16V (1993-1996)



| ENGINE Zetec, R<br>Capacity: 4,25 liter, Filter capacity: 0,5 liter |                          |                          |  |
|---------------------------------------------------------------------|--------------------------|--------------------------|--|
| USE                                                                 |                          | CLIMATE                  |  |
| Normal                                                              |                          | Moderate                 |  |
| PRODUCT RECOMMENDATION 1                                            | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |  |
| Emperol 5W-40                                                       | Emperol 10W-40           | Asyntho 5W-30            |  |

Change every 15000 km/ 12 months

| TRANSAXLE AUTOMATIC CD4E 4/1<br>Capacity: 7,2 liter |                          |          |
|-----------------------------------------------------|--------------------------|----------|
| USE                                                 |                          | CLIMATE  |
| Normal                                              |                          | Moderate |
| PRODUCT RECOMMENDATION 1                            | PRODUCT RECOMMENDATION 2 |          |
| SP Matic 4016                                       | ATF Dexron II-D          |          |
|                                                     |                          |          |

Check every 15000 km/ 12 months

| TRANSAXLE MANUAL MTX75 5/1<br>Capacity: 2,6 liter |   |          |
|---------------------------------------------------|---|----------|
| USE                                               |   | CLIMATE  |
| Normal                                            |   | Moderate |
| PRODUCT RECOMMENDATION 1                          |   |          |
| SP Gear 5015                                      |   |          |
| Check every 15000 km/ 12 months                   | • |          |

| HYDRAULIC BRAKE SYSTEM    |                          |          |
|---------------------------|--------------------------|----------|
| USE                       |                          | CLIMATE  |
| Normal                    |                          | Moderate |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |          |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4       |          |

Change every 36 months

| POWER STEERING                  |                          |          |
|---------------------------------|--------------------------|----------|
| USE                             |                          | CLIMATE  |
| Normal                          |                          | Moderate |
| PRODUCT RECOMMENDATION 1        | PRODUCT RECOMMENDATION 2 |          |
| SP Matic 4016                   | ATF Dexron II-D          |          |
| Check every 15000 km/ 12 months |                          | ·        |

## FORD (EU) MONDEO MK I+II MONDEO 1.8I 16V (1993-1996)



| COOLING SYSTEM<br>Capacity: 6,6 liter |                          |          |
|---------------------------------------|--------------------------|----------|
| USE                                   |                          | CLIMATE  |
| Normal                                |                          | Moderate |
| PRODUCT RECOMMENDATION 1              | PRODUCT RECOMMENDATION 2 |          |
| Coolant SP 11                         | Coolant -38 Organic NF   |          |
|                                       | :                        |          |

Change every 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.