FORD (EU) MONDEO MK IV MONDEO 2.0 TDCI DURATORQ (100 KW) (2010-2015)



| ENGINE UKBA DW Duratorq Capacity: 6,45 liter (Dry fill), Capacity: 5,65 liter (Service fill), Filter capacity: 0,27 liter | | | |
|--|---|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | | | |
| Duranza LSP 5W-30 | | | |
| Change every 20000 km/ 12 months | ¢ | - | |

| CLIMATE |
|----------|
| Moderate |
| |
| |
| |

| TRANSAXLE MANUAL MMT6 6/1 Capacity: 1,75 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Gear 1081 | |

| TRANSAXLE SEMI-AUTOMATIC MPS6/6DCT450 (PowerShift) 6/1 Capacity: 6-7,25 liter | | | |
|--|--|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | | | |
| SP Matic 2072 | | | |
| Change avery 60000 km/26 months | | • | |

Change every 60000 km/ 36 months

| Normal Moderate | HYDRAULIC BRAKE SYSTEM FROM 04/2012 ONWARDS | | |
|---------------------------|---|--|----------|
| PRODUCT RECOMMENDATION 1 | USE | | CLIMATE |
| | Normal | | Moderate |
| | PRODUCT RECOMMENDATION 1 | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-LV Super DOT 4 | | |

Change every 24 months

FORD (EU) MONDEO MK IV MONDEO 2.0 TDCI DURATORQ (100 KW) (2010-2015)



| HYDRAULIC CLUTCH SYSTEM | |
|---------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid-LV Super DOT 4 | |
| | |

Change every 24 months

| POWER STEERING | |
|--------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Fluid 3013 | |

| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF | |
|--|--------------------------|--------------------------|--|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Normal | | Moderate | |
| USE | | CLIMATE | |
| COOLING SYSTEM Capacity: 8,14 liter | | | |
| COOLING SYSTEM | | | |

Change every 120 months

AIRCONDITIONING COMPRESSOR

Capacity: 200 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM Capacity: 510-530 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.