

FORD (EU) S-MAX MK I S-MAX 1.8 TDCI DURATORQ (74 KW) (2006-2008)

**ENGINE FFWA**

Capacity: 6,1 liter (Initial fill), Capacity: 5,6 liter (Service fill), Filter capacity: 0,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Duranza LSP 5W-30***Change every 20000 km/ 12 months***TRANSAXLE MANUAL MMT6 6/1**

Capacity: 1,75 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1081****TRANSAXLE MANUAL MTX75 5/1**

Capacity: 1,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90****HYDRAULIC BRAKE/CLUTCH SYSTEM****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4***Change every 24 months***POWER STEERING****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Fluid 3013***Check every 40000 km/ 24 months*

FORD (EU) S-MAX MK I S-MAX 1.8 TDCI DURATORQ (74 KW) (2006-2008)

**COOLING SYSTEM**

Capacity: 7,93 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 40000 km/ 12 months, change every 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.