FORD (EU) S-MAX MK I S-MAX 2.0 ECOBOOST SCTI (149 KW) (2010-2015)



ENGINE TNWA MI4 EcoBoost Capacity: 5,4 liter, Filter capacity: 0,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Duranza ECO 5W-20	Duranza LSP 5W-30	
		· · · · · · · · · · · · · · · · · · ·

Change every 20000 km/ 12 months

TRANSAXLE MANUAL MMT6 6/1 Capacity: 1,75 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1081	

TRANSAXLE SEMI-AUTOMATIC MPS6/6DCT450 (PowerShift) 6/1 Capacity: 6-7,25 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 2072				

Change every 60000 km/36 months

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		
Change every 24 months	'	

CLIMATE
Moderate

FORD (EU) S-MAX MK I S-MAX 2.0 ECOBOOST SCTI (149 KW) (2010-2015)



COOLING SYSTEM Capacity: 6,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Change every 120 months		

AIRCONDITIONING COMPRESSOR

Capacity: 200 CM3, Capacity: 250 CM3 (With auxiliary climate control)

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 585-615 grams, Capacity: 835-865 grams (With auxiliary climate control)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.