

# FORD (EU) S-MAX MK I S-MAX 2.0 TDCI DURATORQ (120 KW) (2010-2015)

**ENGINE** TXWA DW Duratorq

Capacity: 6,45 liter (Initial fill), Capacity: 5,65 liter (Service fill), Filter capacity: 0,27 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Duranza LSP 5W-30***Change every 20000 km/ 12 months***TRANSAXLE MANUAL** MMT6 6/1

Capacity: 1,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1081****TRANSAXLE SEMI-AUTOMATIC** MPS6/6DCT450 (PowerShift) 6/1

Capacity: 6-7,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2072***Change every 60000 km/ 36 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4***Change every 24 months***POWER STEERING**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Fluid 3013**

# FORD (EU) S-MAX MK I S-MAX 2.0 TDCI DURATORQ (120 KW) (2010-2015)



## COOLING SYSTEM

Capacity: 8,14 liter (+ heater)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

Change every 120 months

## AIRCONDITIONING COMPRESSOR

Capacity: 200 CM3, Capacity: 250 CM3 (With auxiliary climate control)

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING SYSTEM

Capacity: 585-615 grams, Capacity: 835-865 grams (With auxiliary climate control)

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*