FORD (USA) CONTOUR CONTOUR 2.0 16V

(1994-1997)



ENGINE Capacity: 4,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Asyntho 5W-30	
Change every 5000 miles/ 6 months	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Asyntho 5W-30	

	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
ATF Almirol	ATF Dexron II-D

Check every 15000 miles, change every 30000 miles

Change every 3000 miles/ 3 months/ 200 hours

TRANSAXLE MANUAL 5/1 Capacity: 1,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D
Check every 6 months	-	1

HYDRAULIC BRAKE SYSTEM		
USE	С	LIMATE
Normal	N	Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 12 months, change every 24		

FORD (USA) CONTOUR CONTOUR 2.0 16V

(1994-1997)



POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D
Check every 6 months		

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 18	
Check every 15000 miles, change every 30000 miles/ 3	86 months
USE	CLIMATE
First change only	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 18	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.