PRODUCT RECOMMENDATION

FORD (USA) ESCAPE, 2ND GEN ESCAPE
2.5 16V (2012-2012)

ENGINE Duratec 25
Capacity: 5 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		

Check every 1 months, change every 10000 miles/ 12 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		

Change every 5000 miles/ 6 months

TRANSAXLE AUTOMATIC
Capacity: 8,5 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	**SP Matic 2032**	

Change every 150000 miles

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	**SP Matic 2032**	

Change every 30000 miles/ 3 months

TRANSAXLE MANUAL
Capacity: 2,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	**Syngear TDL 75W-90**	**Syngear 75W-90**

Change every 150000 miles

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	**Syngear TDL 75W-90**	**Syngear 75W-90**

Change every 30000 miles/ 3 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

FORD (USA) ESCAPE, 2ND GEN ESCAPE
2.5 16V (2012-2012)

HYDRAULIC BRAKE SYSTEM		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Drauliquid DOT 3**		

COOLING SYSTEM Capacity: 7 liter		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Coolant SP 15+**	PRODUCT RECOMMENDATION 2 **Coolant SP 12**	PRODUCT RECOMMENDATION 3 **Coolant -38 Organic NF**
Check every 6 months, change every 80000 km/ 36 months		
USE Initial service		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Coolant SP 15+**	PRODUCT RECOMMENDATION 2 **Coolant SP 12**	PRODUCT RECOMMENDATION 3 **Coolant -38 Organic NF**
Check every 6 months, change every 160000 km/ 72 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367