Change every 30000 miles/3 months

FORD (USA) ESCAPE, 3RD GEN C1 ESCAPE 2.5 16V (2013-2016)



ENGINE Duratec 25 Capacity: 5,4 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		
Check every 1 months, change every 1000	00 miles/ 12 months	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		
Check every 1 months, change every 5000) miles/ 6 months	

TRANSAXLE AUTOMATIC Capacity: 8,5 liter (Dry fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	
Change every 150000 miles		·
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4036	SP Matic 2032	

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	

FORD (USA) ESCAPE, 3RD GEN C1 ESCAPE 2.5 16V (2013-2016)



COOLING SYSTEM Capacity: 8,7-9,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	
Check every 6 months, change eve	ery 80000 km/ 36 months	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	

AIRCONDITIONING COMPRESSOR Capacity: 133 CM3

Check every 6 months, change every 160000 km/72 months

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 760 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.