

FORD (USA) EXPLORER EXPLORER 4.0 V6 4X4 (2006-2010)

**ENGINE**

Capacity: 4,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30

Change every 5000 miles/ 6 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30

*Change every 3000 miles/ 3 months/ 200 hours***DIFFERENTIAL FRONT (4x4)**

Capacity: 1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

Change every 150000 miles

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

*Change every 60000 miles***DIFFERENTIAL REAR**

Capacity: 1,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 100000 miles

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 50000 miles

FORD (USA) EXPLORER EXPLORER 4.0 V6 4X4 (2006-2010)

**TRANSFERBOX**

Capacity: 1,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Change every 150000 miles

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

*Change every 60000 miles***TRANSMISSION AUTOMATIC 5R55S 5/1**

Capacity: 11,7 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

*Change every 150000 miles***TRANSMISSION AUTOMATIC 6R60 (ZF 6HP26) 6/1**

Capacity: 11,6 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

*Change every 150000 miles***HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 12 months, change every 24 months

FORD (USA) EXPLORER EXPLORER 4.0 V6 4X4 (2006-2010)



POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 6 months

GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

Check every 5000 miles

COOLING SYSTEM

Capacity: 11,5 liter, Capacity: 13,2 liter (with 4 zone airconditioning system)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 11	

Check every 15000 miles, change every 100000 miles/ 60 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 11	

Check every 15000 miles, change every 50000 miles/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.