FORD (USA) FLEX FLEX 3.5 ECOBOOST V6 AWD (2010-2011)



ENGINE EcoBoost Capacity: 5,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30

Change every 10000 miles/ 12 months

DIFFERENTIAL REAR Capacity: 1,15 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	

Change every 150000 miles

	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
SP Matic 2032	

Change every 150000 miles

TRANSFERBOX Capacity: 0,53 liter	
use Normal	climate Moderate
PRODUCT RECOMMENDATION 1 Gearlube Racing 75W-140	

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
use Normal		сымате Moderate
PRODUCT RECOMMENDATION 1 Drauliquid DOT 3		

FORD (USA) FLEX FLEX 3.5 ECOBOOST V6 AWD (2010-2011)



COOLING SYSTEM Capacity: 13 liter		
USE		CLIMATE
Normal, green fluid		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Change every 50000 miles/ 36 months		
USE		CLIMATE
First change only, green fluid		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Change every 100000 miles/ 72 months		
USE		CLIMATE
First change only, orange fluid		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Change every 100000 miles/ 72 months	}	
USE		CLIMATE
Normal, orange fluid		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Change avery 50000 miles/26 menths		

Change every 50000 miles/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.