FORD (USA) FLEX FLEX 3.5 ECOBOOST V6 AWD (2013-2016)



| | CLIMATE | |
|--------------------------|----------|--------------------------|
| | Moderate | |
| PRODUCT RECOMMENDATION 2 | | |
| Xedoz FE 5W-30 | | |
| | | PRODUCT RECOMMENDATION 2 |

Change every 10000 miles/ 12 months

| USE | CLIMATE |
|------------------------------------|----------|
| Severe | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Gearlube GL-5 80W-90 | |
| Change every 3000 miles/ 36 months | |
| USE | CLIMATE |
| Filled for life | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Gearlube GL-5 80W-90 | |

| TRANSAXLE AUTOMATIC 6F55 6/1 Capacity: 11 liter (Dry fill) | | | |
|--|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| SP Matic 4036 | SP Matic 2032 | | |
| | | | |

Change every 150000 miles

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Matic 4036 | SP Matic 2032 | |
| | | |

Change every 30000 miles/3 months

FORD (USA) FLEX FLEX 3.5 ECOBOOST V6 AWD (2013-2016)



| TRANSFERBOX Capacity: 0,53 liter | |
|----------------------------------|----------|
| USE | CLIMATE |
| Filled for life | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Gearlube Racing 75W-140 | |

| HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.) | | |
|---|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid-LV Super DOT 4 | | |
| Change every 24 months | ' | |

| | CLIMATE |
|--------------------------|----------|
| | Moderate |
| PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15+ | |
| | |

Change every 50000 miles/36 months

| use First change only | | climate Moderate |
|--------------------------|--------------------------|---------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15 | Coolant SP 15+ | |

Change every 100000 miles/72 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.