

# FORD (USA) FUSION FUSION 3.5 V6 (2010-2011)



**ENGINE** Duratec 35  
Capacity: 5,2 liter

| USE            | CLIMATE  |
|----------------|----------|
| Flexible (max) | Moderate |

PRODUCT RECOMMENDATION 1

**Duranza ECO 5W-20**

*Check every 1 months, change every 10000 miles/ 12 months*

**TRANSAXLE AUTOMATIC** 6F35 6/1  
Capacity: 8,5 liter (Dry fill)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Matic 4036**

PRODUCT RECOMMENDATION 2

**SP Matic 2032**

*Change every 150000 miles*

**TRANSAXLE AUTOMATIC** Aisin Warner F21 6/1  
Capacity: 7 liter (Dry fill)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Matic 4026**

*Change every 150000 miles*

## TRANSAXLE MANUAL

Capacity: 2,87 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90**

PRODUCT RECOMMENDATION 3

**Syngear 75W-90**

*Change every 150000 miles*

## HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3**

# FORD (USA) FUSION FUSION 3.5 V6 (2010-2011)



## POWER STEERING

Capacity: 0-0 liter (Between min and max.)

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Matic 2032</b>     |  |          |

## COOLING SYSTEM

Capacity: 10,5 liter

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

*Change every 50000 miles/ 36 months*

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| First change only        |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

*Change every 100000 miles/ 72 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.