## FORD (USA) MUSTANG, 5TH GEN MUSTANG GT 5.0 V8 TRACK PACK (2013-2014)



| ENGINE Ti-VCT<br>Capacity: 7,6 liter |          |
|--------------------------------------|----------|
| USE                                  | CLIMATE  |
| Severe                               | Moderate |
| PRODUCT RECOMMENDATION 1             |          |
| Emperol 5W-50                        |          |
| Change every 5000 miles/ 6 months    |          |
| USE                                  | CLIMATE  |
| Flexible (max)                       | Moderate |
| PRODUCT RECOMMENDATION 1             |          |
| Emperol 5W-50                        |          |
|                                      |          |

Change every 10000 miles/ 12 months

| DIFFERENTIAL REAR LIMITED SLIP<br>Capacity: 1,9 liter, Capacity: 118 CM3 (special additive) |          |  |
|---|----------|--|
| USE   | CLIMATE  |  |
| Normal  | Moderate |  |
| PRODUCT RECOMMENDATION 1  |          |  |
| Gearlube Racing 75W-140   |          |  |

| TRANSMISSION AUTOMATIC 6R80 6/1<br>Capacity: 11,2 liter |                          |          |
|---|--------------------------|----------|
| USE   |                          | CLIMATE  |
| Normal  |                          | Moderate |
| PRODUCT RECOMMENDATION 1                                | PRODUCT RECOMMENDATION 2 |          |
| SP Matic 4036   | SP Matic 2032            |          |
| Change every 150000 miles                               |                          |          |

## FORD (USA) MUSTANG, 5TH GEN MUSTANG GT 5.0 V8 TRACK PACK (2013-2014)



| TRANSMISSION MANUAL MT82 6/1<br>Capacity: 2,6 liter |          |
|---|----------|
| USE   | CLIMATE  |
| Normal  | Moderate |
| PRODUCT RECOMMENDATION 1                            |          |
| SP Gear 1081  |          |
| Change every 150000 miles                           |          |
| USE   | CLIMATE  |
| Severe  | Moderate |
| PRODUCT RECOMMENDATION 1                            |          |
| SP Gear 1081  |          |
| Change every 50000 miles                            |          |

| HYDRAULIC BRAKE/CLUTCH SYSTEM<br>Capacity: 0-0 liter (Between min and max.) |         |     |
|---|---------|-----|
| USE   | CLIMATE |     |
| Normal  | Modera  | ate |
| PRODUCT RECOMMENDATION 1  |         |     |
| Drauliquid-LV Super DOT 4   |         |     |

| COOLING SYSTEM<br>Capacity: 12,3 liter |                          |          |
|--|--------------------------|----------|
| USE                                    |                          | CLIMATE  |
| Normal                                 |                          | Moderate |
| PRODUCT RECOMMENDATION 1               | PRODUCT RECOMMENDATION 2 |          |
| Coolant SP 15                          | Coolant SP 15+           |          |
| Change every 50000 miles/ 36 months    |                          |          |
| USE                                    |                          | CLIMATE  |

| USE                                   |                          | CLIMATE  |
|---------------------------------------|--------------------------|----------|
| First change only                     |                          | Moderate |
| PRODUCT RECOMMENDATION 1              | PRODUCT RECOMMENDATION 2 |          |
| Coolant SP 15                         | Coolant SP 15+           |          |
| Change avery 100000 miles / 72 months |                          |          |

Change every 100000 miles/ 72 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.