FORD (USA) MUSTANG, 5TH GEN MUSTANG SHELBY GT500 (2010-2010)



| ENGINE Capacity: 6,1 liter | |
|-------------------------------------|----------|
| USE | CLIMATE |
| Flexible (max) | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Emperol 5W-50 | |
| Change every 10000 miles/ 12 months | |

| DIFFERENTIAL REAR LIMITED SLIP Capacity: 2 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Gearlube Racing 75W-140 | |
| Change every 150000 miles | · |

| TRANSMISSION MANUAL Tremec TR-6060 6/1 Capacity: 3,5 liter | | | |
|--|----------|--|--|
| USE | CLIMATE | | |
| Normal | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | |
| SP Matic 2032 | | | |
| Change every 150000 miles | <u> </u> | | |

| HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.) | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid DOT 3 | |

| POWER STEERING Capacity: 0-0 liter (Between min and max.) | | | | |
|---|----------|--|--|--|
| USE | CLIMATE | | | |
| Normal | Moderate | | | |
| PRODUCT RECOMMENDATION 1 | | | | |
| SP Matic 2032 | | | | |

FORD (USA) MUSTANG, 5TH GEN MUSTANG SHELBY GT500 (2010-2010)



| COOLING SYSTEM Capacity: 20 liter, Capacity: 3,75 liter (intercooler) | | | | |
|---|--------------------------|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| Coolant SP 12 | Coolant SP 11 | | | |
| Change every 45000 miles/ 36 month | าร | | | |
| USE | | CLIMATE | | |
| First change only | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| Coolant SP 12 | Coolant SP 11 | | | |
| Change every 105000 miles/ 72 mon | ths | | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.